



UPPER DECK:
 PERIMETER FRAME
 WORK LIGHT AT REAR OF NECK

MAIN DECK:
 23" LOADED DECK HEIGHT
 8" LOADED GROUND CLEARANCE
 2 FAB I-BEAMS 15"
 1-3/4" APITONG DECKING, RAISED, CNTR OPEN
 10" I-BEAM ON 24" CNTRS.
 6 BENT D-RINGS PER SIDE
 SWINGOUT REMOVABLE OUTRIGGERS ON 24" CNTRS.
 1 PAIR OF FLATBACK OUTRIGGERS
 2" X 10" OAK OUTRIGGER PLANKS

WHEEL AREA:
 33" LOADED DECK HEIGHT
 2S1M ABS WITH AIR BRAKE ON 4 AXLES
 215/75R/17.5 TIRES
 ALUMINUM MILLED INSIDE
 ALUMINUM POLISHED OUTSIDE
 WALKING BEAM SUSPENSION
 TRUNNION AXLES
 BEAVERTAIL WITH TRACTION AIDS
 3 TAIL LIGHT PACKAGE

ADDITIONAL:
 WHITE PAINT
 SINGLE DONUTS
 EXPANDABLE WHEEL AREA TO EXTEND FROM 102" WIDE TO 120" WIDE
 8" AIR CYLINDERS TO EXPAND AND RETRACT WHEEL AREA
 BOLSTERS BETWEEN AXLES TO BE 40" WIDE
 5' BUCKET WELL WITH STEEL PLATED BOTTOM
 LED LIGHTING
 4" AMBER STROBE AS 3RD TAIL LIGHT W/SWITCH
 TOOLBOX AT FRONT OF MAIN DECK WITH STEEL BOTTOM
 STEEL REAR LOADING RAMPS

LOAD RATING ON TRAILER
 100,000 LBS DISTRIBUTED
 100,000 LBS IN 15 CONCENTRATED

DRAWING APPROVAL
 This drawing is forwarded for your approval. Please check all dimensions before signing.
 FIRM: _____
 BY: _____
 DATE: _____

XLSPECIALIZED TRAILERS
 1086 South 3rd St. Manchester, IA 52057

Tolerances:
 Hole Hole Position (Dim.)
 Ang. Tol: ±1°
 Dim. Tol: ±1/16"

THIS DRAWING IS THE PROPERTY OF XL SPECIALIZED TRAILERS WHICH CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL DISCLOSED. IT IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY AND MAY NOT BE COPIED OR USED FOR MANUFACTURING OF ANYTHING SHOWN WITHOUT SPECIFIC WRITTEN PERMISSION OF XL SPECIALIZED TRAILERS

XL 100 MGX MIDCO			
INITIALS JS	DWG. NO. 18001 SD	JOB NUM.	
SIZE D	SCALE N.T.S.	DATE 8/7/18	REV 1
SUSPENSION WALKING BEAM		TIRES 215/75/17.5	