

PREVIOUS CHASSIS NO.637467

THE FOLLOWING LIST DESCRIBES ALL COMPONENTS USED FOR THIS CHASSIS
DIMENSIONS AND WEIGHTS FOR THE ENTIRE ORDER ARE STATED IN CUSTOMARY.

APPLICATION

COMMODITY HAULED 0091170 TRANSPORTATION EQUIPMENT
INTENDED SERVICE 0093110 WRECKER

BODY

BODY TYPE 0095250 WRECKER
BODY LENGTH 336.00 IN BODY HEIGHT 150.00 IN
MAX LADEN WEIGHT 20000.00 LBS

TRAILER

TRAILER TYPE
TRAILER LENGTH .00 FT TRAILER HEIGHT .00 FT
KINGPIN .00 IN CTR LINE AXLE GRP .00 IN
CORNER RADIUS .00 IN NO TRAILER AXLES 00

OPERATING AREA RESTRICTIONS

LENGTH 65.00 FT WIDTH 102.00 IN HEIGHT 13.50 FT
**** DEALER ASSIGNED:

CHASSIS

FRONT AXLE LOAD 14320.00 LBS REAR AXLE LOAD 40000.00 LBS GCW 90000.00 LBS
WHEELBASE 322.00 IN FAX/BOC 92.80 IN CAB/AXLE 229.20 IN
CAB/EOF 299.20 IN MAXIMUM GRADE 06 PERCENT HIGHWAY 100 % CLASS B 000
% CLASS C 000
% CLASS D 000

UNIT TYPE 2

SPECIAL REQUIREMENTS
SPECIAL RESTRICTIONS 0098170 UNITED STATES REGISTRY

ENGINEERING ASSIGNED RATINGS

GAWR FRONT: 14,320.00 LBS
GAWR FIRST INTER 20,000.00 LBS SECOND INTER 20,000.00 LBS
GAWR REAR: 0.00 LBS
GVWR: 54,320.00 LBS

DESCRIPTION

BASE MODEL

MODEL 389 CONVENTIONAL
THE CODES LISTED IN N01XX LINES WERE
NOT VALID FOR THIS MODEL OR YOUR
DESCRIPTION DID NOT PROVIDE ADEQUATE
INFORMATION FOR A CODE TO BE DETERMINED
YOU SHOULD CONTACT THE OPTION APPROVAL
GROUP FOR A VALID CODE OF THE OPTION
DESIRED. A SALES CHANGE NOTICE WILL
BE REQUIRED TO HAVE THE OPTION ADDED
TO THIS ORDER.
5069660, 5456966
NOT APPLICABLE
SECONDARY MANUFACTURER
IDENTICAL PREV FRAME LAYOUT CONFIRMED

FRAME AND EQUIPMENT

10-3/4" STEEL RAILS 403-444" P
3/8" RAIL THICKNESS
WRECKER MAN/MODEL
25T SLEEPER 191" QID 3323
FULL STEEL INNER LINER P
USE W/10-1/2, 10-3/4, 10-5/8" RAILS
ZINC COATED ANTI CORROSION TREATED FRME P
RAILS - REQUIRES FRAME RAIL CODE
FRAME RAKE EXCEEDS RECOMMENDED
CONTACT APPLICATIONS IF UNACCEPTABLE
EOF SQUARE WITHOUT XMBR
USE WITH BODY BUILDER INSTALLED XMBR
OMIT REAR MUDFLAPS & HANGERS

FRONT AXLE AND EQUIPMENT

DANA SPICER E1462I 14,600 LB, 3.5" DROP P
TAPER LEAF SPRINGS, SHOCKS 14,600 LB
POWER STEERING TRW TAS85
POWER STEERING RESERVOIR, FRAME MOUNTED P
W/COOLER
PHP10 ALUMINUM PRESET+ HUBS - AIR DISC
USE WITH FRONT AXLE
GREASABLE FRONT SPRING PINS
DANA SPICER 5" DROP IPO 3.5"

UNIT TYPE 2

DESCRIPTION

DANA SPICER WIDE TRACK IPO STD
FRONT AXLE(S)
AIR DISC FRONT BRAKES
10 MM FRONT SPRING SPACER BLOCKS

REAR AXLE AND EQUIPMENT

DANA SPICER DSP41 40,000 LB
REAR AXLE APPROVED
AE0092580DA
GCW SET TO 90K PER DANA
PHP10 ALUMINUM PRESET+ HUBS
LONG STROKE PARKING BRAKES
DRIVE AXLE(S)
LUBE PUMP, DRIVE AXLE(S)
SBM VALVE
STABILITY SYSTEM NOT SELECTED
OR NOT AVAILABLE
ANTI-LOCK BRAKING SYSTEM (ABS) 6S6M
SYNTHETIC AXLE LUBRICANT ALL AXLES
AIR DISC REAR BRAKES, TANDEM DRIVE AXLE P
DIFF LOCK TANDEM AXLES
WITH SPEED INTERLOCK
RATIO 4.11 REAR AXLE
PETERBILT AIR TRAC 40,000 LBS, 54" AS
DASH MTD DUMP SWITCH WITH INDICATOR
LIGHT FOR SUSPENSION

ENGINE AND ENGINE EQUIPMENT

X15 500@1800 GOV@1800 1650@1000
EFFICIENCY SERIES (2017 EMISSIONS)
ENGINE IDLE SHUTDOWN TIMER DISABLED
ENABLE EIST AMBIENT TEMP OVERRULE
ENABLE EIST IN PTO MODE
EFF EIST NA EXPIRATION MILES
EFFECTIVE VSL SETTING NA
REMOTE PTO & THROTTLE PROVISION
12-PIN CONNECTOR ON ENGINE HARNESS
CARB ENGINE IDLING COMPLIANCE
N205 75...STANDARD MAXIMUM SPEED LIMIT
N207 0....EXPIRATION DISTANCE (N207)
P112 120...HARD MAXIMUM SPEED LIMIT (P1
P001 68...MAXIMUM ACCELERATOR PEDAL VE
P059 68...MAXIMUM CRUISE SPEED (P059)
N203 474...RESERVE SPEED FUNCTION RESET
N202 0....MAXIMUM CYCLE DISTANCE (N202)
N206 10...MAXIMUM ACTIVE DISTANCE (N20
N201 0....RESERVE SPEED LIMIT OFFSET (
P015 YES...ENGINE PROTECTION SHUTDOWN (
P026 NO...GEAR DOWN PROTECTION (P026)
P046 1400..MAX PTO SPEED (P046)
P062 NO....CRUISE CONTROL AUTO RESUME (
P068 NO....AUTO ENGINE BRAKE IN CRUISE
N209 0....EXPIRATION DISTANCE (N209)

UNIT TYPE 2

DESCRIPTION

P520 YES...ENABLE IDLE SHUTDOWN PARK BR
P030 5.....TIMER SETTING (P030)
P233 YES...ENABLE IMPENDING SHUTDOWN WA
P234 60.....TIMER FOR IMPENDING SHUTDOWN
P516 35.....ENGINE LOAD THRESHOLD (P516)
P031 NO....IDLE SHUTDOWN MANUAL OVERRUL
P230 YES...ENABLE HOT AMBIENT AUTOMATIC
P172 40....LOW AMBIENT TEMPERATURE THRE
P173 60....INTERMEDIATE AMBIENT TEMPERA
P171 80....HIGH AMBIENT TEMPERATURE THR
200 AMP ALTERNATOR, STANDARD BRUSH
IMMERSION TYPE BLOCK HEATER 110-120V
SEE SALES TOOL DESC FOR PLUG LOCATION
PACCAR 12V STARTER
N/A PACCAR MX ENGINES
3 PACCAR PREMIUM 12V DUAL PURPOSE
BATTERIES, 2190 CCA
BATTERY JUMPER TERMINAL
MTD UNDER HOOD LH FRAME RAIL
LVD (LOW VOLTAGE DISCONNECT)
CAB & SLEEPER
2-SPEED FAN CLUTCH FOR FREQUENT
START/STOPS
NATURALLY ASPIRATED 18.7 CFM AIR
COMPRESSOR X15 ONLY
INTEBRAKE
ISX/ISX15 (FURNISHED ON ENGINE)
PACCAR FUEL/WATER SEPARATOR STANDARD
SERVICE INTERVAL
NO FLUID HEAT OPTION FOR FUEL FILTER
12V HEAT FOR FUEL FILTER
ENGINE PROTECTION SHUTDOWN
W/DASH LABEL
HIGH EFFICIENCY COOLING SYSTEM
(2) 13" SS AIR CLEANERS,COWL MTD,SS CAP P
EXHAUST DUAL SOC, LH SOC STACK
AESTHETIC ONLY, DPF/SCR RH U/CAB (2017)
CURVED TIP STANDPIPE(S)
CHROME FINISH OVER ELBOWS
FOR DUAL EXHAUST
MUFFLER GUARD / FAIRING STAINLESS STEEL P
HALF ROUND
7" CHROME PLATED STL STANDPIPE(S IPO 5" P
36" HT, 5" DIA STANDPIPE(S) P
CHROME WITH CLEAR COAT

TRANSMISSION AND CLUTCH

EATON RTLO16918B 18-SPEED
EXT OIL-TO-WATER COOLER, INTERNAL PUMP
SPL250 LITE HT DRIVELINE, 3 MIDSHIP
BEARINGS

UNIT TYPE 2

DESCRIPTION

SPL170 XL DRIVELINE INTERAXLE
FOR TANDEM REAR AXLES
(1) DASH MTD SINGLE ACTING AIR PTO CTRL P
MANUAL SHIFTER, CHROME
NEUTRAL START SWITCH
MANUAL TRANSMISSION
HD INPUT BEARING FOR PTO OPERATION
SELF-ADJUST CLUTCH IPO EASY PEDAL
PRE-DAMPED CLUTCH
REMOTE LUBE HOSES FOR CLUTCH LINKAGE
RELEASE BRG & CROSS SHAFTS, MTD TO LH

AIR AND TRAILER EQUIPMENT

BENDIX AD-IS EP AIR DRYER, HEATER
COALESCING FILTER, EXTENDED PURGE
PULL CORDS ALL AIR TANKS
WRECKER A&E CONNECT EOF ON MOVABLE XMBR P
DASH MTD AIR TOGGLE VALVE PLUMBED TO
NYLON CHASSIS HOSE
STEEL PAINTED AIR TANKS
POLISH ALUM AIR TANKS OUTSIDE FRM RAILS P

TIRES AND WHEELS

FF: BR 16PLY 11R24.5 R250ED
PART: BR11R245HR250ED
RR: BR 16PLY 11R24.5 M726ELA
PART: BR005315
CODE-REAR TIRE QTY 08.
FF: ALCOA 985657 24.5X8.25 CLEAN BUFF
ALM, SEVERE SERVICE
RR: ALCOA 985657 24.5X8.25 CLEAN BUFF
ALM, SEVERE SERVICE
CODE-REAR RIM QTY 08.
FF: POLISH WHEELS, OUTER SURFACE,
SGL OR TDM STEER, W/O CHROME WHEEL NUTS
RR: POLISH WHEELS, OUTER SURFACE,
TANDEM DRIVE, W/O CHROME WHEEL NUTS

FUEL TANKS

26" ALUM 70 GAL FUEL TANK RH BOC
26" ALUM 90 GAL FUEL TANK LH U/C
NON-SLIP FUEL TANK STEP LH U/C
LOCATION LH UNDER CAB 090 GAL.
LOCATION RH BEHIND CAB 070 GAL.
POLISH (1) NON-SLIP FUEL TANK STEP
U/C TANK ONLY
POLISH (2) ALUMINUM FUEL TANKS
POLISH ALL FUEL / HYDRAULIC TANK STRAPS P
DEF TANK MOUNTED LH BOC
LESS THAN STD DEF TO FUEL RATIO 2:1
GREATER THAN MINIMUM 1:1

UNIT TYPE 2

DESCRIPTION

POLISHED SS COVER FOR DEF TANK
DEF TANK SMALL

BATTERY BOX AND BUMPER

ALUMINUM SPACE SAVER BATTERY BOX LH BOC P
BATTERY ACCESS FROM SIDE
POLISH BATTERY/TOOL BOX(S)
AFTERTREATMENT CAB ENTRY, COMPLETE
AFTERTREATMENT RH U/C ALUM NON-SLIP
CAB ENTRY STEP
STEEL BUMPER DEEP TAPERED CHROMED
2 TOW PINS

CAB AND EQUIPMENT

ALUMINUM CAB, 123" BBC ALUM HOOD SFFA
W/POLISHED CROWN & SPRING TILT ASSIST
THERMAL INSULATION PACKAGE IN CAB
PETERBILT KEYLESS ENTRY
44" LOW ROOF SLPR W/PRESTIGE INTERIOR
POWER DOOR LOCK ON SLEEPER
RH SLEEPER BAGGAGE DOOR
POLISHED STAINLESS STEEL SLEEPER VENTS
THERMAL INSULATION PACKAGE
44/58" LOW ROOF
PETERBILT ULTRARIDE DRIVER SEAT
PETERBILT ULTRARIDE PASSENGER SEAT
DRIVERS ARMRESTS - LH & RH
PASSENGER ARMREST - LH ONLY
BLACK SEAT COLOR IPO STD COLOR
AIR RIDE DRIVER
HIGH BACK DRIVER
VINYL DRIVER
AIR RIDE PASSENGER
HIGH BACK PASSENGER
VINYL PASSENGER
STEERING WHEEL WITH PETERBILT LOGO
PLATINUM INTERIOR - ARCTIC GRAY
RUBBER FLOOR IPO CARPET - PLAT/PREMIER
INTERIOR FOR CAB
FIXED REAR WINDOW BOS DARK TINT
TWO-PIECE FLAT WINDSHIELD
#REQUIRES MANAGEMENT APPROVAL ON M.D.#
COMBO FRESH AIR HEATER/AIR CONDITIONER
SLPR HEAT/AIR COND W/CONTROLS IN SLPR P
44" (REQUIRES 7322010)
PB COMFORT CONTROL - CAB
OUTSIDE SUNVISOR - STAINLESS STEEL
N/A W/ 2.1M HR SLEEPER
AERO MIRRORS EA SIDE HTD & MTRZD 4-WAY
ADJUSTABLE BRIGHT FINISH WITH CONVEX
(2) AIR HORNS 24.5" CHROME - ROUND
INCLUDES POLISHED HORN SHIELDS

UNIT TYPE 2

DESCRIPTION

MIDLEVEL SPEAKER PACKAGE FOR CAB
(4) SPEAKERS
MIDLEVEL SPEAKER PACKAGE FOR SLEEPER
(2) SPKRS; AVAIL W/44" SLPR ONLY
CB TERMINALS/WIRING MTD UNDER HEADER
CB ANTENNA MOUNTING RH/LH MIRROR
N/A WITH RAMI
SIRIUS-XM SATELLITE RADIO SRV PROVIDER
SmartLINQ REMOTE DIAGNOSTICS
RADIO ANTENNA MTD ON LH MIRROR BRKT
N/A W/RAMI SYSTEM
PB ELEC WINDSHIELD WIPERS
W/INTERMITTENT FEATURE
FIRE EXTINGUISHER, MTD IN SLEEPER
BAGGAGE COMPARTMENT,UL LISTED/RATED ABC
TRIANGLE REFLECTOR KIT
SHIP LOOSE
ANTI-THEFT SYSTEM
BACKUP ALARM (87-112 DB)
VARIABLE ADJUSTING
MAIN TRANSMISSION TEMPERATURE GAUGE
ENGINE OIL TEMPERATURE
LOCATED IN SMARTNAV DISPLAY
MAIN TRANSMISSION OIL TEMPERATURE
LOCATED IN SMARTNAV DISPLAY
AXLE TEMPERATURE GAUGES, TANDEM DRIVE
ENGINE OIL TEMPERATURE GAUGE
GUARD(S) FOR REAR AXLE HEAT GAUGE
AIR APPLICATION GAUGE
AIR RESTRICTION INDICATOR MTD ON AIR
CLEANER, INTAKE PIPING, OR FIREWALL
BUZZER ON AIR SUSPENSION DUMP VALVE
MANIFOLD PRESSURE, BOOST
LOCATED IN SMARTNAV DISPLAY
DPF STATUS
LOCATED IN SMARTNAV DISPLAY
FUEL ECONOMY
LOCATED IN SMARTNAV DISPLAY
PERCENT TORQUE
LOCATED IN SMARTNAV DISPLAY
MANIFOLD PRESSURE GAUGE
SUSPENSION PRESSURE GAUGE
MAIN INSTRUMENTATION PANEL
GRAPHICS DISPLAY
HEADLIGHTS PROJECTOR MODULE POD
INTEGRAL TURN SIGNALS
(5) MARKER LIGHTS, AERO LED
SWITCH & WIRING F/O AUXILIARY LIGHT
UNDER CAB/SLEEPER (15A MAX)
SWITCH & WIRING F/O AUXILIARY LIGHT
ON DUAL AIR CLEANERS

UNIT TYPE 2

DESCRIPTION

SWITCH & WIRING FOR F/O BEACON/STROBE
10' WIRE BOC/BOS AT REAR SILL
SWITCH ON DASH FOR LIGHT IN SLEEPER
IN ADDITION TO STANDARD SWITCH
LED STOP/TURN/TAIL/BACKUP
BRACKET MOUNTED LH/RH EOF
MOVEABLE EOF XMBR FOR MTG TAILLIGHTS
WITH OR WITHOUT EOF XMBR & SQUARE EOF

PAINT

STANDARD PAINT COLOR SELECTION
(1) COLOR AXALTA TWO STAGE
CAB/HOOD/SLEEPER
A - L0006EY WHITE
FRAME L0001EA BLACK
FENDER L0006EY WHITE
HOOD TOP L0006EY WHITE
CAB ROOF L0006EY WHITE
SLEEPER ROOF L0006EY WHITE
SK FAIRINGS L0006EY WHITE
SHIPPING DESTINATION OTHER THAN DEALER
(SPECIFY BY NARRATIVE)
8999990 CVS (JERR DAN PDI CENTER)
8999990 15409 MOLLY PITCHER HIGHWAY
8999990 GREENCASTLE PA 17225
8999990 JIM WINSLOW 717-494-7102

MISCELLANEOUS

44" SLEEPER / PLATINUM INTERIOR (3P)
2017 EPA EMISSIONS ENGINE
WARRANTY ONLY
PRESENTATION CREATED USING FEATURED
SPEC FOR MODEL
PDI AT CVS LOCATION
FRAME LAYOUT IDENTICAL TO PREVIOUS