

XL SLIDE AXLE



FEATURES

- Save time with the quick moving sliding axle assembly
- 6 1/2 degree load angle for loading pavers & rollers
- Versions available with lengths of 48', 51' and 53'
- · California legal and R-tac legal specs available
- Chain drops down the outer and inner beams
- 20,000 lb winch with 100' of 9/16" cable
- Front winch pulls inoperable equipment





SLIDING AXLE ASSEMBLY

The XL Slider features an extended dump angle of 17 degrees and improved hydraulics to keep your equipment from unnecessary wear. Hydraulic sliding axle assembly with traveling bumper provides under ride protection.

USER-FRIENDLY FEATURES

Haul forklifts with the durable 4-inch and 3-inch jr. i-beam crossmembers on 8-inch centers. Enjoy new standard features: chain slots down the outer and center beams, a 2-function wireless remote, and composite rollers that do not need to be greased.



DESIGNED FOR YOU. BUILT TO LAST.

LIDE AXLE SPECS

CAPACITY

capacity: 80,000 lb overall concentrated: 50,000 lb in 10'

OVERALL LENGTH & WIDTH

overall length: 48', 51' or 53' overall width: 102"

UPPER DECK

10' 5" full-width goosneck
49" 5th wheel height
82" swing clearance
21" king pin setting
1 3/8" Apitong decking - raised
2 toolboxes in upper deck with steel doors

1 recessed cable roller, back of neck chain drops on 48" centers, both sides hydraulics run off of wet kit hydraulic control levers 2 speed landing gear

20,000 lb hydraulic winch with manual kickout, & 100' of 9/16" cable with loop

planetary drive 2 function wireless remote

UPPER DECK OPTIONS

length: 37' 7", 40' 7", 42' 7: 5th wheel height other than

28hp unit with dual hydraulics mark V 2 speed landing gear hydraulic park stands

15,000 lb hydraulic planetarty drive winch with 1/2" cable & loop

30,000 lb hydraulic planetary drive winch with 9/16" cable & loop

air kickout for winch

6 function wireless winch remote

7 function wireless remote, for use with air kickout option

10 function wireless remote, for use with air kickout & dock levelers registration holder

MAIN DECK T-1 flange, 80K web

(4) fabricated i-beams
38" loaded deck height
1 recessed cable roller in front
1 3/8" Apitong decking - raised
4" jr i-beam & 3" jr i-beam cross
members on 8" centers
chain drops on 24" centers, each side
double chain drops down the center
energy chain to protect air, electric,
and hydraulic lines
6 1/2° load angle
48' OAL: 17° dump angle
51' OAL: 16° dump angle
53' OAL: 15° dump angle

MAIN DECK OPTIONS

9' wide
10' wide
dock levelers
stake pockets alternating with chain
slots on 12 " centers, outer
beams
additional bent d-rings
pan-style d-rings
drop down d-rings
amber strobe as third taillight

SUSPENSION

25,000 lb air ride manual dump valve

SUSPENSION OPTIONS

liquid filled air gauge Air-Weigh digital scale

AXLES

(2) 25,000 lb nominal 50" axle spacing hub pilot, outboard drums 12 1/4" x 7 1/2" brakes auto slack adjusters limit chains on all axles 2S1M spring brakes on 1 axle greaseless rollers on sliding axle assembly

AXLE OPTIONS

60" axle spacing chassis uni lube system cam covers hubometer dust shields spring brakes on 2nd axle

WHEELS & TIRES

6.75 x 17.5 steel rims 245 / 70R / 17.5 tires

WHEEL & TIRE OPTIONS

235/75R/17.5 tires 245/70R/17.5 michelin tires 255/70R/22.5 16pr radial (deck height + 4.5") PSI tire inflation system aluminum polished wheels aluminum Durabright wheels

LIGHTING

12V sealed Grote harness rubber mounted LED lights 2 tail light package with aluminum cover 2 clearance lights per side 1 mid-turn light per side 7 pole electric socket

PAINT

black, IH red, CAT yellow or white air & electric done after paint

PAINT OPTIONS

non-standard paint colors non-standard metallic paint

WARRANTY

5 year structural 3 year paint

AVAILABLE MODELS

XL 80 SA: California legal XL 80 SA: R-tac legal XL 110 SA